Uni-Pro Painting Equipment Product: Linseed Oil Putty Page 1 of 5

# **Material Safety Data Sheet**

## **SECTION 1. PRODUCT IDENTIFICATION**

Product name: Linseed Oil Putty

Synonym: Wood Filler, Glazing Putty Product Codes: 3404, 3417, 3445, 3420

Manufacturer: UNI-PRO PAINTING EQUIPMENT

Supplier Address: Units 9-12, 144-150 Canterbury Road, Kilsyth VIC 3137

Supplier Contact: Customer Service
Telephone: 03 9761 7900
Fax: 03 9761 6522

### **SECTION 2. HAZARD IDENTIFICATION**

Based on available information, this material is not classified as hazardous according to criteria of Safe Work Australia.

Poison Schedule: Not Applicable

### DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

## **SECTION 3. COMPOSITION INFORMATION**

Chemical Entity	CAS Number	PROPORTION
Ingredients determined to be Non-Hazardous	-	100%

## **SECTION 4. FIRST AID MEASURES**

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and

loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at

rest until fully recovered. Seek medical advice if effects persist.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to

seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink.

Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water.

Seek medical advice.

PPE for First Aiders: Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from

nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before

storing or re-using.

Notes to physician: Treat symptomatically.

Uni-Pro Painting Equipment Product: Linseed Oil Putty Page 2 of 5

# **Material Safety Data Sheet**

## **SECTION 5. FIRE-FIGHTING MEASURES**

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol

resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained

breathing apparatus and suitable protective clothing if risk of exposure to vapour or

products of combustion or decomposition.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Small Spills: Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of

vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal

in properly labelled containers or drums for disposal.

Large Spills: Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up

immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

### **SECTION 7. HANDLING AND STORAGE**

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from

foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep

containers closed when not in use - check regularly for spills.

## **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous

Substances (Safe Work Australia)" the ingredients in this material do not have a

Biological Limit Allocated.

**Engineering Measures:** Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES. Personal protective

equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted. When handling individual retail packs no personal protection equipment is required. Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated

clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or

smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of Issue: 08 JUL 21

Issued by: Uni-Pro Painting Equipment Pty Ltd.

Uni-Pro Painting Equipment Product: Linseed Oil Putty Page 3 of 5

# **Material Safety Data Sheet**

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Flash Point (°C): N Av Putty Form: White Colour: Flammability Limits (%): N Av Odour: Characteristic Auto-ignition Temperature (°C): N Av Solubility: Insoluble in water Melting Point/Range (°C): N Av Specific Gravity (20 °C): Boiling Point/Range (°C): N Av N Av **Density:** N Av pH: N App Relative Vapour Density (air=1): >1 Viscosity: N App Vapour Pressure (20 °C): N Av Total VOC (g/Litre): N Av

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

## **SECTION 10. STABILITY AND REACTIVITY**

**Chemical stability:** This material is thermally stable when stored and used as directed.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

**Hazardous reactions:** No known hazardous reactions.

# **SECTION 11. TOXICOLOGICAL INFORMATION**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

**Eye contact:** May be an eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

### **Acute toxicity**

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5 mg/L

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Uni-Pro Painting Equipment Product: Linseed Oil Putty Page 4 of 5

# **Material Safety Data Sheet**

## **SECTION 11. TOXICOLOGICAL INFORMATION - CONTINUED**

**Chronic Toxicity** 

**Mutagenicity:** This material has been classified as non-hazardous. **Carcinogenicity:** This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

## **SECTION 12. ECOLOGICAL INFORMATION**

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on

ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly

degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or

BCF < 500 and/or log Kow < 4.

Ecotoxicity:No information available.Persistence and degradability:No information available.Bioaccumulative potential:No information available.Mobility:No information available.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

# **SECTION 14. TRANSPORT INFORMATION**

**Road and Rail Transport:** Not classified as Dangerous Goods by the criteria of the "Australian Code for

the Transport of Dangerous Goods by Road & Rail" and the "New Zealand

NZS5433: Transport of Dangerous Goods on Land".

Marine Transport: Not classified as Dangerous Goods by the criteria of the International Maritime

Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport: Not classified as Dangerous Goods by the criteria of the International Air

Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Date of Issue: 08 JUL 21

Issued by: Uni-Pro Painting Equipment Pty Ltd.

Uni-Pro Painting Equipment Product: Linseed Oil Putty Page 5 of 5

# **Material Safety Data Sheet**

## **SECTION 15. REGULATORY INFORMATION**

## This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

## This material/constituent(s) is covered by the following requirements:

· All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

## **SECTION 16. OTHER INFORMATION**

Date of last review: 08 JULY 2021

THE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTENT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

Issued by: Uni-Pro Painting Equipment Pty Ltd.