Uni-Pro Painting Equipment Product: Feronite Rust Converter Page 1 of 5

# **Material Safety Data Sheet**

#### **SECTION 1. PRODUCT IDENTIFICATION**

Product name: Feronite Rust Converter

Product Codes: 420, 421, 422

**Uses(s):** Feronite Rust Converter is used to stop rust increasing or spreading in high temperature

situations where elaborate substrate preparation is impractical. It converts the surface rust

to a passive tannate form.

Manufacturer: UNI-PRO PAINTING EQUIPMENT

Supplier Address: Units 9-12, 144-150 Canterbury Road, Kilsyth VIC 3137

**Supplier Contact:** Customer Service **Telephone:** 03 9761 7900

# **SECTION 2. HAZARD(S) IDENTIFICATION**

Irritant - Category 2
Eye Irritant - Category 2

Signal Word	Hazard Statements	Precautionary Statements
Warning	Causes skin irritation.	Wear protective gloves IF ON SKIN. Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse.
Warning	Causes eye irritation.	Wear eye protection. IF IN EYES – Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing.
Warning	May cause respiratory irritation.	Avoid breathing mist or spray. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

DG Class	9 Exempt from DG Code requirements for Road and Rail transport in Australia.
Subsidiary Risk	None

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS Number	Proportion
Isopropyl Alcohol	67-63-0	< 10%
Phosphoric Acid	7664-38-2	< 10%

There are no other ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, or have been assigned a workplace exposure limit and hence require reporting in this section.

Uni-Pro Painting Equipment Product: Feronite Rust Converter Page 2 of 5

# **Material Safety Data Sheet**

#### **SECTION 4. FIRST AID MEASURES**

**Ingestion:** If swallowed, rinse mouth with water (only if person is conscious). Give plenty of water to

drink. Seek medical attention if symptoms occur.

**Eye Contact:** Immediately flush eyes with running water for at least 15 minutes, keeping eye lids open.

Seek medical attention.

Skin Contact: Take off contaminated clothing. Wash with soap and water. Get medical attention if

symptoms occur.

Inhalation: If inhaled, remove to fresh air. Seek medical attention if symptoms occur.

Note to Physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled.

**Likely Symptoms:** 

**Ingestion:** Irritating to mouth, throat and stomach.

Eye: Redness and pain

**Skin:** Irritating. Repeated or prolonged contact may cause redness, blistering and dermatitis.

**Inhalation:** No known acute effect after over-exposure to this product.

#### **SECTION 5. FIRE FIGHTING MEASURES**

**Extinguishing Media:** Small Fire – Use dry chemical or CO2

Large Fire - Use water, foam or dry chemical powder.

**Specific Hazards:** The product will not support combustion unless the water has evaporated.

No specific hazards.

**Fire Fighters:** Contaminated water should be prevented from entering waterways, drains or sewers.

Hazchem Code: 2ZE

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Small Spills: Absorb spillage with sand, earth, or any suitable absorbent material.

Large Spills: Prevent material from entering waterways, drains or sewers. Consider bunding. Use sand or

earth to absorb the material. Allow water content to evaporate and dispose of residual solid

material as solid waste.

### SECTION 7. HANDLING, STORAGE AND SAFE USE

**Handling:** Use with adequate ventilation.

Vapour is heavier than air.

Use suitable protective equipment. Avoid contact with eyes, skin and clothing.

Eating, drinking and smoking in work areas is prohibited.

**Storage:** Keep away from incompatibles such as bases.

Sensitive to frost.

High temperatures can reduce shelf life. Has a nominal shelf life of 1 year.

Suitable Packaging Materials: High Density Polyethylene

Uni-Pro Painting Equipment Product: Feronite Rust Converter Page 3 of 5

# **Material Safety Data Sheet**

# **SECTION 8. EXPOSURE CONTROLS**

	Material	TWA		STEL	
Francisco Lincito		ppm	mg/m³	ppm	mg/m³
Exposure Limits	IPA	400	983	500	1230
	Phosphoric Acid		1		3
Engineering Controls	Use only with adequate ventilation.				
Personal Protection	Safety glasses with side shields Nitrile Rubber Gloves Clothing which covers arms, legs and torso. In case of inadequate ventilation, wear suitable respiratory equipment Advice on personal protection equipment is applicable for high exposure levels. Select proper personal protection based on a risk assessment of the actual exposure situation.				

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance Brown aqueous liquid

Odour Strong smell
pH 1.6-2.0

Melting Point/Freezing Point (°C) -3°C

Boiling Point and boiling range (°C) 100°C

Flash Point (°C) Not applicable

Flammability The product will not support combustion unless the water has evaporated.

Upper/lower lammability or

explosive limits

Not applicable

 Vapour pressure (20°C)
 4.4kPa @ 20°C

 Rel. Vapour Density (air=1)
 2.07 @ 20°C

 Relative Density
 1.06 – 1.09

 Solubility
 100% in water

Viscosity 50 cP

## **SECTION 10. STABILITY AND REACTIVITY**

**Chemical Stability** Stable under recommended storage and handling conditions. Reactive materias.

**Incompatible Materials** Reactive with metals and bases, strong oxidising materials.

**Hazardous Decomposition** 

**Products** 

Combustion products include CO, CO2, NOx, Ammonia, HCI, Cl2

Product: Feronite Rust Converter Page 4 of 5

# **Material Safety Data Sheet**

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Acute Effects	Ingestion	Irritating to mouth, throat and stomach LD50 rat (oral) > 5,000n	
	Eye	Irritating, watering, redness	
	Skin	Irritating, redness	
	Inhalation	No known specific effects or critical hazards	

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous the environment.

## **SECTION 13. DISPOSALS CONSIDERATIONS**

Waste must be disposed of in accordance with national and local environmental regulations.

Dispose of all empty containers as per State and Council Regulations.

Do not burn empty containers.

Do not dispose of near waterways, vegetation and tree roots.

#### **SECTION 14. TRANSPORT INFORMATION**

Not classified as hazardous or dangerous for transport. Hazchem Code 2ZE

# **SECTION 15. REGULATORY INFORMATION**

No information.

Uni-Pro Painting Equipment Product: Feronite Rust Converter Page 5 of 5

# **Material Safety Data Sheet**

#### **SECTION 16. OTHER**

Date of last issue: 10th August 2023

Reason for Issue: Revision

Preparation of Safety Data Sheets for Hazardous Chemicals. Code of Practice 2011 Workplace Health and Safety Queensland

Queensland Work Health and Safety Regulation 2011 Workplace Exposure Standards 2011, Safework Australia ADG7 October 2011 Section 2.9.3.3 GHS 2013 5th Edition Health effects 03e\_part3

GHS 2013 5th Edition Environmental Hazards 04e\_part4

**DISCLAIMER:** WE BELIEVE THAT THE INFORMATION GIVEN HEREIN IS ACCURATE AND IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE. WHERE THE INFORMATION PROVIDED HEREIN DISCLOSES POTENTIAL HAZARDOUS INGREDIENTS, ADEQUATE WARNING SHOULD BE PROVIDED TO EMPLOYEES AND USERS AND APPROPRIATE PRECAUTIONS TAKEN.

### **Abbreviations**

ADG7	Australian Code for the Transport of Dangerous goods by Road & Rail, 7th Edition	mg	milligram
C.A.S.	Chemical Abstracts Service Number	Mg/m3	Milligram per cubic metre
EC50	Half Maximal Effective Concentration	No mort	No mortality.
EPG	Emergency procedure guide	N.O.S.	Not Otherwise Specified
ErC50	Means EC50 in terms of reduction of growth rate	NOEC	No observable effect concentration
GHS	Globally Harmonized System of Classification and	ppm	Parts per million
	Labelling of Chemicals		
kg	Kilogram	PVC	Polyvinyl Chloride
L	Litre	Sen	Sensitizer
LC50	Lethal concentration for 50% of the test population	Sk	Sk absorption is significant.
LD50	Lethal dose for 50% of the test population	STEL	Short Term Exposure Limit
LDLo	Least Lethal Dose Observed	TWA	Time Weighted Average
LOEC	Lowest Observable Effective Concentration		