

Product: Uni-Pro Gap Filler

Material Safety Data Sheet

1. Product & Company Identification

Product Details

Product name: UNi-PRO Gap Filler

Physical form: Paste Product Code 3700

Odour: Mild Acrylic Odour

CAS No.: Mixture

Company Details

Manufacturer: UNI-PRO PAINTING EQUIPMENT

Address Units 9-12, 144-150 Canterbury Road, Kilsyth VIC 3137

Tel: 03 9761 7900 Fax: 03 9761 6522

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Serious eye damage or eye irritation	Category 2
Tochoos eye damage or eye inhanon	

Hazard Statement

H319 - Causes serious eye irritation.

<u>Precautionary Statement - Prevention</u>

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

<u>Precautionary Statement - Response</u>

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

<u>Precautionary Statement – Storage</u>

No precautionary statement.

Precautionary Statement - Disposal

No precautionary statement.



Product: Uni-Pro Gap Filler

Material Safety Data Sheet

3. Composition / Hazardous Components

<u>Chemical Name</u>

<u>CAS No.</u>

 Plasticizer
 68515-48-0
 < 5 %</td>

 Ethylene glycol
 107-21-1
 1 - 10 %

 Mineral Spirits
 64742-48-9
 1 - 5 %

Synthetic polymer(s) - 20 – 40% Calcium carbonate 471-34-1 40 – 60%

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.

In case of skin contact:

Wipe with paper towel and immediately clean with water and soap.

In case of eyes contact:

Immediately flush with water, seek medical advice if necessary.

WT%

5. Fire Fighting Measures

Suitable extinguishing media: Water, foam, CO2, dry powder and all standard fire-fighting media.

Unsuitable extinguishing media: Unknown Hazardous decomposition: Not specified.

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Ensure good ventilation during processing. Wear safety shoes.

Protection against fire/explosion: General rules of fire prevention should be observed.

Storage: Keep container tightly closed and dry.

Cautions: Extreme heavy in drum form if product packed in 200L drum.

8. Exposure control / Personal protection

Ingredients with limited values to N

be controlled:

Not indicated.

Local exhaust: Recommended
General ventilation: Recommended

Hand protection: Suitable protective gloves. Eye protection: Safety/protective glasses.



Product: Uni-Pro Gap Filler

Material Safety Data Sheet

9. Physical and Chemical Properties

Form: Paste
Specific gravity: 1.60 ± 0.05
Colour: White

Viscosity: Not indicated.
Odour: Mild Acrylic Odour

Volatile, % wt $(25\, \mbox{$\mathbb{C}$})$: $15\pm 5\, \%$ Solubility in water:SolubleBoiling point: $100\, \mbox{$\mathbb{C}$}$ Flash point:Non knownIgnition temperature:Non known

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability: Stable

Incompatibility (material to be avoid):

Conditions to be avoid:

Dangerous reactions:

None known

None known.

Dangerous products of decomposition: No dangerous decomposition products known.

11. Toxicological Information

Acute toxicity: Not determined

Primary irritant effect,

On the skin: Irritant for skin and mucous membranes.

On the eye: Irritant effect

Additional Toxicological information: When used and handled according to specification, the

product does not have any harmful effects according to our

experience and the information provided to us.

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

Dispose the waste matters and contaminated packaging following law, rules and regulations.

Dispose to an authorised waste collection point.

Do not cast waste (waste fluid, solid waste and washing drainage etc.) that includes this product directly into a river, or bury it underground.



Product: Uni-Pro Gap Filler

Material Safety Data Sheet

14. Transport Information

Proper shipping name: Latex based Acrylic Sealant

Hazard technical name:

Hazard class:

Not available.

No dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements of EC directives.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End of SDS ***